


Correct assembly for silent drag pawl & cam

Ensure that Drag pawl pin is inside of silent drag cam slot or reel will click when winding.

Spring should be in front of pin for correct operation of the drag.

When assembling spool to reel have drag in OFF position.



Key	Part	Description	Key	Part	Description
1	R6E2	Spindle Screw Set	14	R7M4	Drag Pawl Rivet
2	R7F1	Handle-plate Lock Nut	15	R7J4	Drag Pawl
3	R7E22	Handle-plate & Handle	16	R5G3	Drag Pawl Spring
4	R4F17	Power Handle Assy	17	R5K1	On/Off Cam
5	R4F4	Rapid Handle Assy	18	R7K10	On/Off Lever/Activator
6	R7P3	Balance Weight	19	R1A	Reel without Spool
7	R7D12	Tristar Drag Nut	20	R5E10	Ratchet Button
8	R7B/C11	Friction Washer Set	21	R2G12	Base Lock Spring
9	R4A	Spool Only	22	R6F1	Hex Nut
10	R7L3	Silent Drag Cam	23	R2D7	Base Bolt
11	R5B4	Fish Alert Wheel	24	R2A7	Turbo Cast Assembly
12	R7A6	Friction Tube	25	R2L1	Base Bolt Washer
13	R6A17	Spindle	26	R2F1	Base Bolt Nut

6000BCVRR